475 Field Communicator Spare Parts List

Description	Part Number
Ruggedized 250 Ohm Load Resistor	00275-0096-0001
Rechargeable Li-Ion Power Module	00475-0002-0022
Power Supply & Charger (Li-ion/NiMH) US/UK/EU connection types included.	00475-0003-0022
Power Supply/Charger Standard cord set (US/UK/EU cords)	00375-0003-0002
Australian (AU) cord for Power Supply/Charger	00375-0003-0003
Lead Set with connectors	00375-0004-0001
Hand Strap (pack of 2)	00475-0005-0002
Carrying Case (with spare Hand Strap and Stylus)	00475-0005-0003
Magnetic Hanger	00475-0005-0004
Protective Rubber Boot with Stand	00475-0005-0005
Stylus (pack of 2)	00475-0006-0001
IrDA to USB Adapter [1]	00375-0015-0002
System Card (SD) Reader (with USB Interface) [2]	00375-0018-0022
Bluetooth Adapter [1][9]	00475-0018-0023
Stand	00475-0044-0001
Field Accessory Kit[6]	00475-0019-FK01
Shop Accessory Kit (Bluetooth)[7][9]	00475-0019-SK01
Shop Accessory Kit (non-Bluetooth)[7]	00475-0019-SK02
Getting Started Guide	00475-0045-3001
Resource CD	00475-0049-0001
Resource DVD[8]	00475-0049-DVD1
Technical Training CD	00475-0050-TRN1
Online Licensing [4]	
FOUNDATION fieldbus license via Web	00375-0142-0002
Easy Upgrade (New/Renew) license via Web [3]	00475-0142-2003
AMS Device Manager Handheld Interface Kit [5]	
AMS Suite: Intelligent Device Manager Field Communicator Interface Kit (25 tags)	AW7005HC00025
AMS Suite: Intelligent Device Manager Field Communicator Interface Kit (100 Tags and above)	AW7005HC20000

(1) Can be used to support communication between the 375/475 and the Easy Upgrade Programming Utility or AMS Device Manager (with Handheld Communicator Interface Kit). Either IrDA or Bluetooth Communication is required to register the 375/475 or use the Online Licensing system.

(2) The System Card (SD) Reader allows a user the ability to upgrade a System Card much faster than they can when using IRDA or Bluetooth. Due to file size constraints, major upgrades require the use of a card reader.

(3) The *Easy Upgrade* feature allows the user to add new System Application software and Device Descriptions (DDs) to the 475 for a period of 3 years. To upgrade without this feature, the System Card would have to be sent to a Service Center (fee would apply). When purchased, the expiration date becomes three (3) years from the date of the PO of three (3) years from the expiration date of the current license - whichever is greater. Current licenses can only be renewed within 6 months of the expiration date on the current license.

(4) These parts support license upgrades of System Cards in the field through the use of the Field Communicator Online Licensing system. The capability is available to end users and may also be performed by an agent on the user's behalf. It is at the agents discretion if an additional fee should apply. Any order must be accompanied by the System Card S/N. Instant notification of when the licenses are available for download are sent to emails provided at time of order. For further details, see the Online Licensing procedure at www.fieldcommunicator.com.

(5) Requires AMS Device Manager (6.2 or higher). Both AMS Device Manager and the Handheld Communicator Interface Kit are available for sale through select channels only. See www.assetweb.com for further details.

(6) Contains Protective Rubber Boot, Ruggedized 250 Ohm Load Resistor, Magnetic Hanger, Stylus Pack, and Technical Training CD.

(7) Contains Field Accessory Kit plus System Card Reader, Bluetooth Adapter, and Resource CD and DVD. Non-Bluetooth model subsitues IRDA to USB adapter for Bluetooth adapter.

(8) Same content as Resource CD, but also includes localized versions for English. German, Russian, and Japanese.

(9) Not available for purchase from Rosemount - Chanhassen. Use alternative channel to order this part.

Pricing

The listed prices are effective with the date of issue and are subject to change without notice. All prices may be subject to F.O.B. charges from NoveMesto, SK or Knoxville, USA. The prices are exclusive of sales and use tax.

Shipping Weight (varies with options)

5lbs/2.3kg (based on 475HP1EKLUGMTS)

EMERSON™
Process Management