

THREADED GROUNDING FERRULES

Salisbury compression **Threaded Grounding Ferrules** provide low resistant connection to cable strands with a threaded stud that securely screws into a clamp. Nut and lock washers increase contact pressure and secure the assembly. Use aluminum ferrules on aluminum body clamps. Tin plated copper ferrules can be used on either bronze or aluminum body clamps. All Salisbury threaded grounding ferrules are unshrouded and manufactured with a 5/8-11 UNC threaded stud and meets the requirements of ASTM F855.



	Cat. No. Pair	ASTM Grade	Size	Installing Die Codes T&B	Burndy Die Numbers	Weight ea. lbs. (kgs)
ALUMINUM	2026	1	#2	50	-	.2 (.1)
	2027	2	1/0	50	-	.2 (.1)
	2620	3	2/0	60	-	.3 (.1)
	4284	4	3/0	71	-	.3 (.1)
	2640	5	4/0	71	-	.3 (.1)
COPPER	2022	1	#2	50	U243	.5 (.2)
	2023	2	1/0	50	U243	.4 (.2)
	2024	3	2/0	60	U245	.4 (.2)
	4277	4	3/0	66		.6 (.3)
	2025	5	4/0	66	U247	.6 (.3)

Add suffix "A" to the catalog number when requesting a custom insulated grounding set.