

PLAIN SHROUDED & UNSHROUDED FERRULES

Plain Ferrules are designed for use with all grounding clamps that feature pressure terminal including the 1" duckbill and 1.5" flat jaw clamp.

Copper Ferrules are available in two different styles: unshrouded and shrouded. Shrouded ferrules are compressed on both the conductor and the jacket of the cable to reduce bending stress. Unshrouded ferrules are crimped on the conductor strands only. These ferrules are manufactured of tin plated, 99.5% pure copper.

Aluminum Ferrules are available in two different styles: unshrouded and shrouded. Shrouded ferrules are compressed on both the conductor and the jacket of the cable to reduce bending stress. Unshrouded ferrules are crimped on the conductor strands only.

Salisbury plain ferrules meet the requirements of ASTM F855.



plain shrouded



plain unshrouded

	Cat. No. Pair	Cable Size	Strand Die Codes T&B	Jacket Die Codes T&B	Burndy Die Number	Weight ea. lbs. (kgs)
C O P P E R	SHROUDED					
	24424	#2	50	71	-	0.3 (.14)
	24425	1/0	50	71	-	0.35 (.16)
	24426	2/0	60	76	-	0.4 (.18)
	24427	4/0	66	106	-	0.45 (.20)
	UNSHROUDED					
	24420	#2	50	-	-	0.3 (.14)
	24421	1/0	50	-	U243	0.3 (.14)
24422	2/0	60	-	U245	0.35 (.16)	
24423	4/0	66	-	U247	0.35 (.16)	
A L U M I N U M	SHROUDED					
	24434	#2	50	71	-	0.1 (.045)
	24436	2/0	60	76	-	0.15 (.07)
	24437	4/0	71	106	-	0.15 (.07)
	UNSHROUDED					
	24430	#2	50	-	-	0.12 (.54)
	24431	1/0	50	-	-	0.12 (.54)
	24432	2/0	60	-	-	0.16 (.073)
24433	4/0	71	-	-	0.16 (.073)	

Add suffix "A" to the catalog number when requesting a custom insulated grounding set.

SALISBURY

Setting industry standards since 1855. 7520 N Long Ave Skokie IL 60077 Toll Free 877.406.4501 Fax 847.679.2401