

"C" TYPE GROUNDING CLAMPS

1.25" and 1.5" Sizes



Cat. No. & Description		Class / ASTM Grade	Main Line Range	Continuous Current Rating	Weight ea. lbs. (kgs)
1.25" BRONZE "C" CLAMP - Acme Thread					
B R O N Z E	9984	Eye	5 / A		2.2 (1.0)
		w/ strain relief sleeve	Smooth Jaw		
	1897	Eye	w/		2.1 (.9)
		w/o strain relief sleeve	Flat Lower Jaw	1035.5 KCM ACSR	
	4255	Eye	5 / A	to #6	400 RMS Amps
		w/ strain relief sleeve	Smooth Jaw		60Hz
	21069	Eye	w/	1.26 " - .16"	2.1 (.9)
		w/o strain relief sleeve	Curved Lower Jaw		
	4279	Eye	5 / B	32mm - 4mm Dia.	2.2 (1.0)
		w/ strain relief sleeve	Serrated Jaw		
21070	Eye	w/		2.1 (.9)	
	w/o strain relief sleeve	Flat Lower Jaw			
9983	Hanger Stud only				.4 (.2)
1.25" ALUMINUM "C" CLAMP - Acme Thread					
A L U M I N U M	24410	Eye	5 / A	1035.5 KCM ACSR	2.2 (1.0)
		w/ strain relief sleeve	Smooth Jaw	to #6	400 RMS Amps
			w/ Flat Lower Jaw	1.26 " - .16"	60Hz
			32mm - 4mm Dia.		
1.5" ALUMINUM "C" CLAMP, w/ flat lower jaw - Acme Thread					
A L U M I N U M	1895	Eye			1.7 (.8)
		w/ strain relief sleeve			
	2195	Eye		1431 KCM ACSR	1.5 (.7)
		w/o strain relief sleeve	5 / B	to #6	400 RMS Amps
	1896*	Mounted	Serrated Jaw	1.5" - .16"	60 Hz
		w/ strain relief sleeve		to #6	
	21099	"T"		38mm - 4mm Dia.	1.7 (.8)
		w/ strain relief sleeve			
1928	Hanger Stud only				.2 (.1)

*Mounted: 1.25" dia x 6' Fiberglass Hot Stick permanently mounted