

"C" TYPE GROUNDING CLAMPS

2.4" Size



1924 - Stick Mounted "C" Type Clamp

Cat. No. & Description		Class / ASTM Grade	Main Line Range	Continuous Current Rating	Weight ea. lbs. (kgs)	
2.4 " ALUMINUM "C" CLAMP w/ Flat Lower Jaw - Acme Thread						
ALUMINUM	1923 Eye w/ strain relief sleeve	5 / A Smooth Jaw	2.0" I.P.S. to #6	400 RMS Amps 60 Hz	2.1 (1.0)	
	4377 Eye strain relief sleeve & oval eye				2.1 (1.0)	
	4240 Eye w/o strain relief sleeve				2.0 (1.0)	
	1924* Mounted w/ strain relief sleeve				5.1 (2.3)	
	1921 Eye w/ strain relief sleeve	5 / B Serrated Jaw	2.4" - .16" 61mm - 4mm Dia.	400 RMS Amps 60 Hz	2.2 (1.0)	
	4390 Eye strain relief sleeve & oval eye				2.2 (1.0)	
	1922* Mounted w/ strain relief sleeve				5.2 (2.3)	
	1928 Hanger Stud only					
	2.4" BRONZE "C" CLAMP w/ flat lower jaw - Acme Thread					
	BRONZE	4295 Eye w/ strain relief sleeve	5 / A Smooth Jaw	2.0 " I.P.S. to #6	400 RMS Amps 60 Hz	4.1 (1.8)
4311 Eye w/o strain relief sleeve			2.4" - .16" 61mm - 4 mm Dia.		4.0 (1.7)	

*Mounted: 1.25" dia x 6' Fiberglass Hot Stick permanently mounted