

GROUNDING CLAMPS FOR SUBSTATION BUSES



4282



4341



2991

Cat. No. & Description	Class / ASTM Grade	Main Line Range	Continuous Current Rating	Weight ea. lbs. (kgs)
3.5" ALUMINUM "C" CLAMP for Substation Buses - Acme Thread				
4282 Eye		3" - 1.5" I.P.S.		2.8 (1.3)
w/ strain relief sleeve				
4283* Mounted	5 / A	3.5" - 1.75"		5.8 (2.5)
w/ strain relief sleeve	Smooth Jaw	89mm - 44mm Dia.	400 RMS Amps	
4341 Eye, strain relief	w/	3" I.P.S. to #6	60 Hz	2.9 (1.4)
sleeve & long eye screw	Flat Lower Jaw	3.5" - .16"		
(Main line range 3.5"-.16"(89-4mm)		89mm - 4 mm Dia.		
6.62" ADJUSTABLE ALUMINUM " C " CLAMP for Round, Square, Rectangle or "H" Section Substation Buses - Acme Thread				
2991 Eye				6.9 (3.1)
w/ strain relief sleeve				
2993** Eye	5 / A			7.0 (3.2)
w/ single contact stud	Smooth Jaw	6.12" I.P.S.	400 RMS Amps	
9967** Eye	w/	6.62" - .4"	60 Hz	7.3 (3.3)
w/ double contact stud	Flat Lower Jaw	168mm - 10mm Dia.		
4378 Eye, strain relief				6.9 (3.1)
sleeve & oval eye				

*Mounted: 1.25" dia x 6' Fiberglass Hot Stick permanently mounted

**No Ferrule Connection