

PRESSURE TERMINAL CLAMPS

These **Duckbill** and **“C” Clamps** feature pressure terminations for use with plain ferrules. Made of high strength aluminum, with bronze eye-screws, these Grade 5 clamps are designed for smooth operation and long service life. Duckbill clamps for all grounding applications from .16 to 1.1" diameter. “C” clamps for all grounding applications from .06 to 1.26" diameter.

Flat Jaw Grounding Clamps are now available with pressure terminals for use with plain cable ferrules. These clamps are made of a high strength aluminum, and a bronze eye screw or “T” handle for durability and smooth operation. Also featured is a hardened aluminum alloy serrated insert. This insert is designed to grip tightly to flat surfaces and cut through surface contamination and oxidation for low resistance contact. The pressure termination is designed on an angle keeping the cable out of the way during installation. The cable termination is angled to minimize interface with the “T” handle or eye when installing or removing the clamp.



Salisbury’s **24438 Plain Ferrule 4-way Connector** is available on page H-23.

	Cat. No. & Description	Class / ASTM Grade	Main Line Range	Continuous Current Rating	Weight ea. lbs. (kgs)
M U N	1.1" SMOOTH JAW ALUMINUM --Spring Loaded - "V" Thread				
	24404 Duckbill	5 / A Smooth Jaw	795 KCM ACSR	400 RMS Amps 60 Hz	1.5 (.68)
	Eye w/o strain relief sleeve		to #6		
			1.1" - .16" 28mm - 4mm Dia.		
I M U	1.25" SMOOTH JAW ALUMINUM --Spring Loaded - Acme Thread				
	24466 “C” Type	5 / B Serrated	1035.5 KCM ACSR	400 RMS Amps 60 Hz	2.2 (1.0)
	Eye w/o strain relief sleeve		to #6		
			1.26" - .06" 32mm - 1.5mm Dia.		
	24407 Stick mounted duckbill clamp			4.5 (2.05)	
	21754 Hanger Stud only			.3 (.1)	
A L	ALUMINUM FLAT JAW Grounding Clamp - Acme Thread				
	24405 “T” screw	5 / B	1.5" - .06"	400 RMS Amps	2.1 (.9)
	no strain relief sleeve		Flat or Square		
	24406 Eye screw	Serrated Jaw	1.26" - .06"	60Hz	2.0 (.9)
no strain relief sleeve	32 - 1.5 mm Dia.				

SALISBURY

Setting industry standards since 1855. 7520 N Long Ave Skokie IL 60077 Toll Free 877.406.4501 Fax 847.679.2401