

GROUNDING CABLES

Grounding Cables are made with extra flexible strand of soft drawn #30 AWG (.01”) copper and are available in three different jackets.

The yellow thermoplastic elastomer jacketed cable is the standard for grounding service. It provides a combination of economy, flexibility, and durability. The service temperature ranges from 200° to -50°F per ASTM F 855, Type I requirements.

The black thermoplastic elastomer jacketed cable has a smaller diameter and thinner jacket material giving it better flexibility than the yellow cable. The service temperature ranges from 200° to -50°F per ASTM F 855, Type I requirements.

The transparent flexible thermoplastic (PVC or silicone) jacketed cable allows easy inspection for strand breakage. The flexibility decreases with low temperatures. The minimum recommended service temperature is 0°F per ASTM F 855, Type III requirements.



	Cat No.	Size	Strand Dia. in. (mm)	Jacket in. (mm)	Short Circuit Withstand AMPS, RMS, 60Hz		Continuous Current AMPS, RMS, 60Hz	Wt. / 1000 ft. lbs. (kgs)
					15 Cycles	30 Cycles		
YELLOW	2136	#2-665W	.35 (8.9)	.5 (12.7)	14500	10000	200	282 (127)
	2137	1/0-1064W	.45 (11.4)	.62 (15.7)	21000	15000	250	488 (221)
	2138	2/0-1330W	.49 (12.4)	.65 (16.5)	27000	20000	300	537 (243)
	2139	4/0-2109W	.62 (1.7)	.83 (21.1)	43000	30000	400	836 (379)
BLACK	2636	#2-665W	.35 (8.9)	.47 (12)	14500	10000	200	263 (119)
	2637	1/0-1064W	.45 (11.4)	.58 (14.7)	21000	15000	250	404 (183)
	2638	2/0-1330W	.49 (12.4)	.63 (16)	27000	20000	300	497 (225)
	2649	3/0-1672W	.55 (14)	.72 (18.3)	36000	25000	350	680 (308)
	2639	4/0-2109W	.62 (1.7)	.78 (19.8)	43000	30000	400	770 (349)
CLEAR	2128	#2-665W	.35 (8.9)	.53 (13.5)	14500	10000	200	289 (131)
	2129	1/0-1064W	.45 (11.4)	.64 (16.3)	21000	15000	250	520 (235)
	2133	2/0-1330W	.49 (12.4)	.7 (17.8)	27000	20000	300	546 (247)
	2288	4/0-2109W	.62 (1.7)	.84 (21.3)	43000	30000	400	841 (381)
CLEAR SILICONE	21930	2/0-1330W	.49 (12.4)	.62 (15.7)	27000	20000	300	487 (221)
	21931	4/0-2109W	.62 (1.7)	.78 (19.8)	43000	30000	400	579 (263)